

EVA-11S AC Charger

(Three phase - 11kW EV Charger)



COMPACT DESIGN

Attractive appearance, A4 print paper size, simple but elegant.



FULL PROTECTION

Full electrical protection, over/under temperature protection, etc.



STABLE

IP65 protection grade, capable for harsh environment, salt-mist condition.



INTELLIGENT

Intelligent power adjustment, emergency stop, Wifi/APP/ethernet monitoring.



EUROPEAN STANDARD

Ocpp v1.6 standard open communication protocol, IEC 62196 type II connector.



EASY TO INSTALL

Wall-mounting or pole-mounting optional.

Input & Output

Input voltage	400V AC
Input frequency	50Hz
Output voltage	400V AC
Max. output power	11KW
Max. output current	16A
Charging interface type	IEC 62196-2, Type II

Protection

Over voltage protection	Yes
Under voltage protection	Yes
Over load protection	Yes
Short circuit protection	Yes
Earth leakage protection	Yes
Ground protection	Yes
Over-temp protection	Yes
Lightning protection	Yes

Type A RCD plus 6mA DC fault detection and protection



Designed to meet your specific needs...

Standard Price (LAN/Wall Mounting)	Included
Charging Socket	Included
Monitoring/WiFi	Included
RCD/TYPE A	Included
RFID	Included
RFID card	Included
RFID card (additional cards)	Optional
Charging Gun (5m)	Optional
Monitoring/4G	Optional
Mounting/Pole	Optional



Function and Accessory

Ethernet/WIFI/4G	Yes/Opt/Opt
Connector	Gun/Socket
LCD	Opt
RCD	Type A + 6mA DC fault current protection
LED Indicator light	Yes
Emergency stop button	Yes
Intelligent power adjustment	Opt



Environment

IP grade	IP65
Operation temperature	-30°C ~ +55°C
Operation Humidity	5% ~ 95% without condensation
Operation attitude	<2000m
Cooling methods	Natural air cooling
Standby power consumption	<8W



Mechanical

Dimension (L*W*H)	420*270*135mm
Weight	<16KG

Mounting Accessories

Wall-mounting bracket/ Ground-mounting pole	*Pole dimension& weight: 200mm*1200mm*180mm(W*H*D),8.5kg.
--	--

